



STARMUX IV DIGITAL LINK



RACK MOUNT (STARMUX IV DL AND 2U COMPUTER IN 6U CASE)

Size	13.2 cm (5.2 in.) high 48.2 cm (19 in.) wide 50.5.2 cm (20 in.) deep	76.2 cm (30 in.) high 76.2 cm (30 in.) wide 64.9 cm (23.37 in.) deep
Weight	10.4 kg (23 lb.)	70.31 kg (155 lb.)
Case construction	Aluminum 19-inch rack mount	PVC
Shipping Container Type	Carton	Sealed high impact polyurethane case
Shipping Container Size	66 cm (26 in) high 66 cm (26) in wide 30.5 cm (12 in) deep	76.2 cm (30 in.) high 76.2 cm (30 in.) wide 76.2 cm (30 in.) deep
Shipping Weight	14.5 Kg (32 lb.)	70.3 kg (155 lb.)
Operating Temp.	0–45°C (32–113°F)	0–45°C (32–113°F)
Storage Temp.	-10–60°C (14–140°F)	-10–60°C (14–140°F)
Operating relative humidity	5–90% (non-condensing)	5–90% (non-condensing)
Non-operating storage relative humidity	5-90%	5-90%
Input voltage	100-264 VAC, 50/60 Hz, auto-switching	100-264 VAC, 50/60 Hz, auto-switching
Input power	~ 1200W	~ 1200 W
Power to Towfish	375 VDC	375 VDC
Processor	—	Intel Core, I7, 3.6 GHz Quad-Core
Memory	—	4 GB, 1333 MHz
Data storage	—	DVD/RW drive 1-TB hard drive (data) 500-GB hard drive (OS)
Display	—	21-inch LCD monitor
Keyboard	—	High impact industrial keyboard
Pointing device	—	High impact industrial trackball
External trigger		
I/O ports	(4) Ethernet (6) RS-232 (1)PPS Trigger (1)FSK Trigger (2)Trigger	(5) Ethernet (8) RS-232 (6) USB 2 (2) USB 3 (1)PPS Trigger (1)FSK Trigger (2) Trigger

Table 2-3: Starmux IV Specifications